



DEMAG

All Terrain Crane

AC 335






Working Ranges

- Main boom
- Tele-Extension Jib

42 ft — 164 ft

33 ft — 56 ft






Working Ranges

— Main boom

42 ft — 164 ft

— Fixed fly jib


39 ft, 59 ft, 79 ft, 98 ft





Working Ranges

— luffing jib: 59 ft, 79 ft, 98 ft, 118 ft






Specifications

Carrier Performance

Forward Speeds	0 – 44 mph	Reverse Speeds	3.8 mph
Ground clearance	14"		
Tail swing – with 24,000 lb or 60,000 lb counterweight	16'4"		
– with 88,000 lb counterweight	16'10"		

Working Speeds (infinitely variable)

Units	Line Speed	Rope Pull, Single Line	Length of Hoist Rope
Main Hoist	max. 394 ft/min	18,298 lb	984 ft
Secondary Hoist	max. 394 ft/min	18,298 lb	722 ft
Swing	max. 2 RPM		
Telescoping from 42 ft to 133 ft	80 s		
Boom Elevation from –2° to 83°	60 s		



Hook-Block/Crane Hook

Capacity		Number of Sheaves	Number of Lines	Weight	"B"
max.	85%				
353,000 lb	331,000 lb	9	18	3,086 lb	8 ft
221,000 lb	201,000 lb	5	11	2,681 lb	8 ft
139,000 lb	128,000 lb	3	7	2,326 lb	8 ft
88,000 lb	55,000 lb	1	3	1,676 lb	8 ft
28,000 lb	18,000 lb	Crane Hook	1	816 lb	6 ft



Lifting Capacities in 1,000 lb

with outriggers – 360°

24,000 lb Counterweight

85%

Radius	Main Boom								Main Boom 164 ft		Radius
	42 ft	*** 42 ft	72 ft	*** 72 ft	103 ft	133 ft	149 ft	164 ft	Tele-Extension-Boom 0°	56 ft	
ft	lb	lb	lb	lb	lb	lb	lb	lb	lb	lb	ft
9	309.0**	-	-	-	-	-	-	-	-	-	9
11	282.1	-	198.0*	-	-	-	-	-	-	-	11
13	249.1	-	198.0*	-	132.0	-	-	-	-	-	13
15	220.0	35.2	198.0*	34.0	132.0	-	-	-	-	-	15
16	194.0	31.0	187.3*	30.4	129.1	-	-	-	-	-	16
20	156.3	25.1	143.2*	24.4	119.0	79.0	-	-	-	-	20
23	130.0	20.7	113.9	19.8	108.0	72.7	62.0	-	-	-	23
26	110.2	17.2	95.9	16.3	94.7	67.6	58.8	46.0	-	-	26
29	89.0	14.3	77.3	13.2	80.4	62.8	54.8	46.0	-	-	29
33	-	-	64.1	10.8	71.6	58.4	51.1	44.0	-	-	33
39	-	-	49.6	7.0	54.0	49.6	44.5	39.6	25.0	-	39
46	-	-	36.3	4.2	41.6	39.6	39.6	35.4	23.8	18.0	46
52	-	-	28.6	-	32.4	31.9	33.2	31.5	22.2	18.0	52
59	-	-	22.9	-	25.5	25.1	26.6	26.4	20.7	17.1	59
66	-	-	-	-	20.7	19.8	21.6	21.1	18.9	16.0	66
72	-	-	-	-	16.3	15.8	17.4	16.9	16.9	15.2	72
79	-	-	-	-	13.2	12.3	14.1	13.6	14.3	14.1	79
85	-	-	-	-	10.5	9.7	11.4	10.8	11.6	12.7	85
92	-	-	-	-	-	7.4	9.0	8.5	9.0	11.0	92
98	-	-	-	-	-	5.7	7.0	6.6	7.0	9.2	98
105	-	-	-	-	-	3.9	5.2	5.2	10.3	10.1	105
111	-	-	-	-	-	2.6	4.1	3.7	5.5	7.4	111
118	-	-	-	-	-	-	-	2.6	4.0	5.9	118
125	-	-	-	-	-	-	-	-	2.6	4.4	125
131	-	-	-	-	-	-	-	-	-	2.6	131
138	-	-	-	-	-	-	-	-	-	-	138
144	-	-	-	-	-	-	-	-	-	-	144
150	-	-	-	-	-	-	-	-	-	-	150
157	-	-	-	-	-	-	-	-	-	-	157
164	-	-	-	-	-	-	-	-	-	-	164
170	-	-	-	-	-	-	-	-	-	-	170
177	-	-	-	-	-	-	-	-	-	-	177
184	-	-	-	-	-	-	-	-	-	-	184

w/o Counterweight

85%

Radius	Main Boom								Radius
	42 ft	*** 42 ft	72 ft	*** 72 ft	103 ft	133 ft	149 ft	164 ft	
ft	lb	lb	lb	lb	lb	lb	lb	lb	ft
9	276.0	-	-	-	-	-	-	-	9
11	244.7	-	176.0*	-	-	-	-	-	11
13	209.4	-	176.0*	-	121.0	-	-	-	13
15	182.9	26.5	176.0*	25.5	117.5	-	-	-	15
16	160.9	23.1	158.7*	22.2	113.9	-	-	-	16
20	121.2	18.0	121.2	17.0	100.7	70.0	-	-	20
23	85.9	14.1	85.9	13.2	83.7	64.5	55.7	-	23
26	63.9	11.0	61.7	10.1	63.9	59.7	52.0	40.0	26
29	48.5	8.6	48.5	7.5	50.7	50.7	48.5	40.0	29
33	-	-	39.0	5.5	41.2	40.7	41.6	39.0	33
39	-	-	26.4	-	28.4	27.9	31.0	29.1	39
46	-	-	16.7	-	20.5	20.0	22.9	21.1	46
52	-	-	13.6	-	15.4	14.7	17.1	15.8	52
59	-	-	10.1	-	11.6	11.0	13.0	12.1	59
66	-	-	-	-	8.8	8.3	9.9	9.2	66
72	-	-	-	-	6.6	5.9	7.0	6.8	72
79	-	-	-	-	4.4	3.7	5.0	4.6	79
85	-	-	-	-	2.8	1.9	3.3	3.0	85

* only pin-connected

** with heavy lift accessories

*** over rear on tyres

AC 335

Lifting Capacities with Superlift in 1,000 lb with outriggers – 360°

60,000 lb Counterweight

85%

Radius ft	Main Boom					
	42 ft	72 ft	103 ft	133 ft	149 ft	164 ft
9	331.0**	—	—	—	—	—
11	299.8**	198.0	—	—	—	—
13	275.5	198.0	136.5	—	—	—
15	242.5	198.0	135.1	—	—	—
16	219.8	198.0	130.9	—	—	—
20	178.7	177.9	123.6	84.0	—	—
23	149.2	148.1	117.2	80.9	66.0	—
26	127.4	126.3	110.8	78.4	63.4	44.0
29	110.9	109.5	103.8	74.9	60.0	44.0
33	—	96.3	95.4	72.0	57.5	44.0
39	—	74.2	73.4	67.2	53.5	44.0
46	—	58.2	57.3	57.0	50.9	44.0
52	—	46.7	45.8	45.6	48.9	43.2
59	—	38.3	37.7	37.4	40.1	39.9
66	—	—	31.0	30.8	33.0	34.6
72	—	—	26.2	25.8	27.8	29.1
79	—	—	21.6	21.3	23.3	24.9
85	—	—	18.0	17.8	19.6	21.1
92	—	—	—	14.5	16.5	18.0
98	—	—	—	12.1	13.9	15.4
105	—	—	—	9.9	11.7	13.2
111	—	—	—	8.1	9.9	11.2
118	—	—	—	—	8.1	9.7
125	—	—	—	—	6.6	7.9
131	—	—	—	—	5.2	6.6
138	—	—	—	—	—	5.2
144	—	—	—	—	—	4.4
150	—	—	—	—	—	—
157	—	—	—	—	—	—
164	—	—	—	—	—	—
170	—	—	—	—	—	—
177	—	—	—	—	—	—
184	—	—	—	—	—	—

* without Superlift-Suspension!

** only with add. attachment!

Radius ft	Main Boom 164 ft Tele-Extension-Boom 0°	
	33 ft	56 ft
9	—	—
11	—	—
13	—	—
15	—	—
16	—	—
20	—	—
23	—	—
26	—	—
29	—	—
33	—	—
39	25.0	—
46	24.0	17.5
52	23.5	17.5
59	22.7	17.5
66	22.0	17.5
72	21.1	16.3
79	20.0	15.6
85	19.1	14.5
92	18.3	13.8
98	15.8	13.0
105	13.4	12.3
111	11.4	11.6
118	9.7	11.0
125	8.1	9.9
131	6.6	8.3
138	5.3	7.0
144	4.4	6.1
150	3.3	5.0
157	2.4	4.2
164	—	3.3
170	—	2.6
177	—	—
184	—	—



Lifting Capacities with Superlift in 1,000 lb with outriggers – 360°

88,000 lb Counterweight

85%

Main Boom							Main Boom 164 ft		
Radius							Tele-Extension-Boom 0°		Radius
	42 ft	72 ft	103 ft	133 ft	149 ft	164 ft	33 ft	56 ft	
ft	lb	lb	lb	lb	lb	lb	lb	lb	ft
9	331.0**	-	-	-	-	-	-	-	9
11	299.8**	198.0	-	-	-	-	-	-	11
13	275.5	198.0	136.5	-	-	-	-	-	13
15	255.7	198.0	135.1	-	-	-	-	-	15
16	233.7	198.0	130.9	-	-	-	-	-	16
20	199.2	193.6	123.6	84.0	-	-	-	-	20
23	168.4	167.3	117.2	80.9	66.0	-	-	-	23
26	144.1	142.8	110.8	78.4	63.4	44.0	-	-	26
29	125.6	124.3	103.8	74.9	60.0	44.0	-	-	29
33	-	109.5	98.5	72.0	57.5	44.0	-	-	33
39	-	87.9	85.0	67.2	53.5	44.0	25.0	-	39
46	-	72.7	71.8	62.6	50.9	44.0	24.0	17.5	46
52	-	61.0	59.5	58.2	49.3	43.2	23.5	17.5	52
59	-	51.3	50.7	50.7	47.3	40.5	22.7	17.5	59
66	-	-	42.3	42.5	44.0	38.5	22.0	16.9	66
72	-	-	36.3	36.3	37.9	37.4	21.1	16.3	72
79	-	-	31.3	31.3	32.8	34.1	20.0	15.6	79
85	-	-	27.3	27.1	27.7	30.0	19.1	14.5	85
92	-	-	-	23.3	25.1	26.4	18.2	13.8	92
98	-	-	-	20.0	21.8	23.1	16.9	13.0	98
105	-	-	-	17.6	19.1	20.2	16.0	12.3	105
111	-	-	-	15.2	16.5	18.0	15.4	11.6	111
118	-	-	-	-	14.5	15.8	14.3	11.0	118
125	-	-	-	-	12.7	14.1	13.6	10.5	125
131	-	-	-	-	11.4	12.3	12.7	10.1	131
138	-	-	-	-	-	11.0	11.2	9.7	138
144	-	-	-	-	-	9.9	9.9	9.0	144
150	-	-	-	-	-	-	8.5	8.5	150
157	-	-	-	-	-	-	7.7	8.1	157
164	-	-	-	-	-	-	6.6	7.7	164
170	-	-	-	-	-	-	-	7.0	170
177	-	-	-	-	-	-	-	6.1	177
184	-	-	-	-	-	-	-	5.2	184

* without Superlift-Suspension!

** only with add. attachment!

Lifting Capacities on Fixed Fly Jib Boom (3°) and Superlift with outriggers – 360°

88,000 lb counterweight

85%

60,000 lb counterweight

85%

Fixed Fly Jib 3°				Fixed Fly Jib 3°				
Boom	Radius	39 ft	59 ft	Boom	Radius	39 ft	59 ft	79 ft
	ft	lb	lb		ft	lb	lb	lb
164 ft	33	22.7	-	164 ft	33	22.7	-	-
	39	21.8	16.5		39	21.8	16.5	-
	46	21.1	15.8		46	21.1	15.8	13.2
	52	20.5	15.4		52	20.5	15.4	12.3
	59	20.0	15.0		59	20.0	15.0	11.9
	66	19.4	14.5		66	19.4	14.5	11.2
	72	18.5	14.1		72	18.5	14.1	11.0
	79	17.8	13.6		79	17.8	13.6	10.3
	85	17.1	13.2		85	17.1	13.2	9.9
	92	16.5	12.5		92	16.5	12.5	9.7
	98	15.8	12.1		98	15.8	12.1	9.2
	111	14.1	11.4		111	11.9	11.4	8.1
	125	12.3	10.3		125	8.3	9.4	7.0
	138	10.1	9.7		138	5.7	6.4	5.9
	150	8.6	8.3		150	3.7	4.4	4.4
	164	6.6	7.0		164	1.9	2.6	3.0
	170	5.2	6.1		170	-	1.9	2.4
	177	4.4	5.2		177	-	-	1.7



Lifting Capacities in 1,000 lb

with outriggers – 360°

on Luffing Fly Jib

24,000 lb counterweight

75%

Boom	Radius	Luffing Fly Jib			
		59 ft	79 ft	98 ft	118 ft
	ft	lb	lb	lb	lb
72 ft	26	68.0	-	-	-
	29	67.2	-	-	-
	33	66.1	53.0	-	-
	39	52.9	48.5	37.0	-
	46	40.1	44.0	35.4	25.0
	52	30.0	39.2	33.0	23.8
	59	-	31.7	30.4	22.0
	66	-	25.3	28.4	20.5
	72	-	19.8	24.2	18.7
	79	-	14.1	20.0	16.9
	85	-	-	16.3	15.4
	92	-	-	12.7	13.8
	98	-	-	-	12.5
	105	-	-	-	10.8
	111	-	-	-	8.1
103 ft	29	50.0	-	-	-
	33	48.5	-	-	-
	39	45.1	33.0	-	-
	46	41.8	31.9	26.0	-
	52	37.2	30.8	24.9	19.0
	59	27.1	29.7	24.0	18.2
	66	-	28.6	22.9	17.1
	72	-	24.4	22.0	16.5
	79	-	18.5	20.9	16.0
	85	-	-	19.8	15.4
	92	-	-	16.3	15.0
	98	-	-	12.3	14.3
	105	-	-	-	13.4
	111	-	-	-	10.3
	118	-	-	-	7.4
133 ft	125	-	-	-	-
	131	-	-	-	-
	39	27.0	21.0	-	-
	46	25.1	19.6	16.0	-
	52	23.8	18.7	15.2	11.0
	59	22.9	18.0	14.7	11.0
	66	22.4	17.4	14.3	10.1
	72	-	16.7	13.6	9.4
	79	-	16.0	13.2	9.2
	85	-	15.4	12.7	9.0
	92	-	-	12.5	8.8
	98	-	-	12.1	8.8
	105	-	-	-	8.5
	111	-	-	-	8.3
	118	-	-	-	7.9
149 ft	125	-	-	-	-
	131	-	-	-	-
	39	22.0	16.0	-	-
	46	20.9	14.9	11.0	-
	52	19.8	14.3	9.9	5.0
	59	19.1	13.8	9.7	5.0
	66	18.2	13.4	9.2	4.8
	72	-	13.0	9.0	4.6
	79	-	12.5	9.0	4.4
	85	-	12.1	9.0	4.4
	92	-	-	8.8	4.4
	98	-	-	8.8	4.4
	105	-	-	8.8	4.4
	111	-	-	-	4.4
	118	-	-	-	4.4
164 ft	125	-	-	-	4.4
	131	-	-	-	-
	39	-	11.0	8.0	-
	46	-	10.8	7.2	-
	52	-	10.3	7.0	2.2
	59	-	10.1	6.8	1.8
	66	-	-	-	-
	72	-	9.9	6.3	1.5
	79	-	9.7	6.1	1.3
	85	-	9.4	6.1	1.3
	92	-	-	5.9	1.3
	98	-	-	5.9	1.3
	105	-	-	-	-
	111	-	-	5.7	1.3
	118	-	-	-	-

on Fixed Fly Jib

60,000 lb counterweight

85%

Boom	Radius	Fixed Fly Jib							
		39 ft		59 ft		79 ft		98 ft	
		3°	20°	3°	20°	3°	20°	3°	20°
	ft	lb	lb	lb	lb	lb	lb	lb	lb
164 ft	33	24.0	-	-	-	-	-	-	-
	39	23.1	-	17.0	-	-	-	-	-
	46	21.8	-	16.3	-	13.8	-	-	-
	52	20.2	17.0	15.6	-	13.2	-	9.9	-
	59	18.9	16.0	14.9	13.0	12.1	-	9.7	-
	66	17.8	15.2	14.1	11.9	11.4	-	9.0	-
	72	16.9	14.1	13.4	11.4	10.5	9.0	8.5	-
	79	15.6	13.4	12.5	11.0	10.1	8.3	8.1	-
	85	14.3	12.5	11.9	10.3	9.7	8.1	7.7	6.0
	92	13.4	11.9	11.2	9.9	9.0	7.7	7.0	5.9
	98	12.1	11.2	10.3	9.7	8.3	7.2	6.6	5.7
	111	10.1	9.7	8.8	8.8	6.8	6.3	5.7	5.2
	125	8.3	8.1	7.7	7.7	5.2	5.9	4.6	4.4
	138	5.7	6.3	6.3	6.6	4.4	5.5	3.3	3.9
	150	3.7	4.1	4.4	5.5	3.3	4.6	2.8	3.5
	164	1.9	2.4	2.6	3.5	2.4	3.7	1.9	2.8
170	170	-	1.5	1.9	2.6	1.9	3.0	-	2.4
	177	-	-	-	1.7	-	2.4	-	-

24,000 lb counterweight

85%

Boom	Radius	Fixed Fly Jib							
		39 ft		59 ft		79 ft		98 ft	
		3°	20°	3°	20°	3°	20°	3°	20°
	ft	lb	lb	lb	lb	lb	lb	lb	lb
164 ft	33	24.0	-	-	-	-	-	-	-
	39	23.1	-	17.0	-	-	-	-	-
	46	21.8	-	16.3	-	13.8	-	-	-
	52	20.2	17.0	15.6	-	13.2	-	9.9	-
	59	18.9	16.0	14.7	13.0	12.1	-	9.7	-
	66	17.8	15.2	14.1	11.9	11.4	-	9.0	-
	72	16.9	14.1	13.4	11.4	10.5	9.0	8.5	-
	79	14.1	13.4	12.5	11.0	10.1	8.3	8.1	-
	85	11.4	12.5	11.9	10.3	9.7	8.1	7.7	6.0
	92	9.0	11.0	9.7	9.9	9.0	7.7	7.0	5.9
	98	6.8	8.5	7.0	9.7	7.7	7.2	6.6	5.7
	111	3.3	4.6	3.9	5.9	4.4	6.3	4.4	5.2
	125	-	1.9	1.5	3.3	1.9	4.1	2.2	4.4
	131	-	-	-	2.2	-	3.0	-	3.7
	137	-	-	-	-	-	1.9	-	2.6
	144	-	-	-	-	-	-	-	1.7

Lifting Capacity Notes

Lifting capacities do not exceed 85% of tipping load resp. 75% of tipping load on luffing fly jib.

Max. wind speed: 50.85 ft/sec or 35 mph.

Crane operation up to a wind force of 5% Beaufort scale (29.5 ft/sec or 20 mph) permissible.

The weights of all load-handling devices are considered part of the load, and suitable allowance for them should be made

All capacities above the parting line are based on structural strength. The capacities below the parting line are based on stability for the percentage of tipping load indicated



Lifting Capacities in 1,000 lb

with outriggers – 360°

88,000 lb Counterweight

85%

Radius ft	Main Boom					
	42 ft	72 ft	103 ft	133 ft	149 ft	164 ft
9	331.0**	-	-	-	-	-
11	299.8**	-	-	-	-	-
13	275.5	198.0*	132.0	-	-	-
15	255.7	198.0*	132.0	-	-	-
16	233.7	198.0*	129.1	-	-	-
20	199.2	193.5*	119.0	79.0	-	-
23	168.4	167.3*	109.3	72.7	62.0	-
26	144.1	142.8*	99.8	67.6	58.8	49.0
29	125.6	124.3*	92.3	62.8	54.8	46.9
33	-	109.5	85.0	58.4	51.1	44.0
39	-	87.0	73.6	50.9	44.5	39.6
46	-	72.7	67.0	44.7	39.6	35.4
52	-	61.0	57.3	39.9	35.2	31.5
59	-	51.3	50.7	35.9	31.9	27.9
66	-	-	45.1	33.0	28.8	24.4
72	-	-	39.0	29.9	26.2	22.0
79	-	-	33.7	27.3	23.8	19.8
85	-	-	29.7	24.2	22.0	18.2
92	-	-	-	22.0	20.2	16.7
98	-	-	-	19.4	18.9	15.4
105	-	-	-	17.8	17.6	14.3
111	-	-	-	16.5	16.3	13.2
118	-	-	-	-	15.2	12.3
125	-	-	-	-	14.1	11.0
131	-	-	-	-	12.7	9.9
138	-	-	-	-	-	8.8
144	-	-	-	-	-	7.4
150	-	-	-	-	-	-
157	-	-	-	-	-	-
164	-	-	-	-	-	-
170	-	-	-	-	-	-
177	-	-	-	-	-	-
184	-	-	-	-	-	-

Radius ft	Main Boom 164 ft Tele-Extension-Boom 0°	
	33 ft	56 ft
9	-	-
11	-	-
13	-	-
15	-	-
16	-	-
20	-	-
23	-	-
26	-	-
29	-	-
33	-	-
39	25.0	-
46	23.8	18.0
52	22.2	18.0
59	20.7	17.1
66	18.9	16.0
72	16.9	15.2
79	15.4	14.1
85	13.8	12.7
92	12.5	11.9
98	11.4	10.8
105	10.3	10.1
111	9.7	9.4
118	8.3	8.3
125	7.9	7.7
131	7.4	7.2
138	6.8	6.6
144	6.1	6.1
150	5.5	5.5
157	4.8	5.0
164	4.1	4.6
170	-	4.1
177	-	3.7
184	-	3.3

60,000 lb Counterweight

85%

Radius ft	Main Boom							
	42 ft	42 ft ***	72 ft	72 ft ***	103 ft	133 ft	149 ft	164 ft
9	331.0**	-	-	-	-	-	-	-
11	299.8**	-	198.0*	-	-	-	-	-
13	275.5	-	198.0*	-	132.0	-	-	-
15	242.5	44.0	198.0*	43.0	132.0	-	-	-
16	219.7	40.0	198.0*	39.0	129.1	-	-	-
20	178.7	33.0	177.9*	32.1	119.0	79.0	-	-
23	149.2	27.7	148.1*	26.9	109.3	72.7	62.0	-
26	127.4	23.5	126.3*	22.7	99.8	67.6	58.8	49.0
29	110.8	20.2	109.5	19.4	92.3	62.8	54.8	46.9
33	-	-	96.3	16.5	85.0	58.4	51.1	44.0
39	-	-	74.2	11.9	73.6	50.9	44.5	39.6
46	-	-	58.2	8.6	60.1	44.7	39.6	35.4
52	-	-	46.7	6.1	48.7	39.9	35.2	31.5
59	-	-	38.3	4.2	40.1	35.9	31.9	27.9
66	-	-	-	-	33.7	33.0	28.8	24.4
72	-	-	-	-	28.6	27.9	26.2	22.0
79	-	-	-	-	24.4	23.5	23.8	19.8
85	-	-	-	-	20.9	19.8	21.3	18.2
92	-	-	-	-	-	16.9	18.2	16.7
98	-	-	-	-	-	14.1	15.6	15.4
105	-	-	-	-	-	11.9	13.4	13.2
111	-	-	-	-	-	10.1	11.6	11.2
118	-	-	-	-	-	-	9.9	9.7
125	-	-	-	-	-	-	8.3	7.9
131	-	-	-	-	-	-	7.0	6.6
138	-	-	-	-	-	-	-	5.2
144	-	-	-	-	-	-	-	4.4
150	-	-	-	-	-	-	-	-
157	-	-	-	-	-	-	-	-
164	-	-	-	-	-	-	-	-
170	-	-	-	-	-	-	-	-
177	-	-	-	-	-	-	-	-
184	-	-	-	-	-	-	-	-

Radius ft	Main Boom 164 ft Tele-Extension-Boom 0°	
	33 ft	56 ft
9	-	-
11	-	-
13	-	-
15	-	-
16	-	-
20	-	-
23	-	-
26	-	-
29	-	-
33	-	-
39	25.0	-
46	23.8	18.0
52	22.2	18.0
59	20.7	17.1
66	18.9	16.0
72	16.9	15.2
79	15.4	14.1
85	13.8	12.7
92	12.5	11.9
98	11.4	10.8
105	10.3	10.1
111	9.7	9.4
118	8.3	8.3
125	7.9	7.7
131	7.4	7.2
138	6.8	6.6
144	6.1	6.1
150	5.5	5.5
157	4.8	5.0
164	4.1	4.6
170	-	4.1
177	-	3.7
184	-	3.3



* - standard

** with heavy lift accessories

*** over load in tons



Dimension Chart



* Width with more than 60,000 lb counterweight 14'5" tail swing 16'11"