



TM 3851
19 USt Lifting Capacity
Boom Truck Crane
Datasheet
Imperial

TM 3851



Features

- ▶ 19 USt @ 5 ft capacity at rated distance from center of rotation
- ▶ 51 ft maximum boom length
- ▶ 61 ft maximum tip height
- ▶ 18/29 ft optional jib
- ▶ 90 ft maximum tip height with 29 ft jib
- ▶ Quick reeving dual sheave boom head

WORKS FOR YOU.™



CONTENTS

TM 3851

Page:

Key

..... 3

Dimensions

Crane Dimensions 4, 5

Area of Operations 5

Mounting Specification 5

Range Diagram 6

Load charts

Boom Load Charts 7

Jib, Retracted & Extended 7

Technical description

Boom, Jib and Rotation 8

Operator Controls 8

Understructure 9




























Optional Features 9





KEY

TM 3851


	Main boom		Main Hoist
	Boom length		Hoist line speed
	Tip height		Part line
	Telescoping mode		Operator aid
	Boom angle		Controls
	Working radius		Hydraulics
	Boom with jib		Working temperature
	Boom head		Outriggers
	Hook block		Rotation / Allowable rotation range
	Hook to head sheave pin		Boom angle
	Rope - Standard / Optional		Boom over the rear
	Rope diameter		Boom over the front
	Rope length		Working speeds
	Line pull		



DIMENSIONS

TM 3851

Crane Dimensions







DIMENSIONS

TM 3851

Crane Dimensions



Area of Operation



Mounting Specifications



Gross Vehicle Weight Rating	52,000 lb
Front Axle Weight Rating.....	18,000 lb
Rear Axle Weight Rating	34,000 lb
Wheelbase	230 +/- 8 in
Cab to Axle.....	162 +/- 6 in
Afterframe.....	114 +/- 6 in
RBM per Frame Rail.....	1,800,000 lb/in



RANGE DIAGRAM

TM 3851


Outriggers Fully Extended (100%)



BOOM LOAD CHARTS

TM 3851


Outriggers Fully Extended (100%)



Standard ASME B30.5

ft	Boom Length					ft
	21 lb	29 lb	36 lb	43 lb	51 lb	
5	38,000					5
8	28,200	25,550	24,850			8
10	24,000	22,700	21,900	17,800	17,400	10
12	20,900	19,800	19,000	15,400	15,000	12
14	18,300	17,500	16,800	13,500	13,100	14
16	16,000	15,700	15,100	12,100	11,700	16
19	11,400	13,500	13,100	10,400	10,100	19
23		11,000	11,000	8,725	8,425	23
27		6,625	9,325	7,425	7,225	27
30			8,025	7,225	6,525	30
34			4,825	6,225	5,725	34
38				5,025	5,425	38
41				3,125	4,825	41
45					4,025	45
49					2,425	49


Boom at 0°



Standard ASME B30.5

°	Boom Length					°
	21 lb	29 lb	36 lb	43 lb	51 lb	
0	9,000	6,000	4,000	2,800	2,000	0

With Jib, Retracted and Extended



Standard ASME B30.5

ft	Jib Capacities for All Boom Lengths								ft	
	80° lb	75° lb	70° lb	65° lb	60° lb	55° lb	50° lb	45° lb		40° lb
18	6,025	4,825	3,725	2,825	2,225	1,825	1,625	1,425	1,025	18
29	3,825	3,025	2,325	1,825	1,425	1,125	925	825	725	29

Notes to lifting capacity

Lifting capacities do not exceed 85% of tipping load. Weight of hook blocks and slings is part of the load, and is to be deducted from the capacity ratings. Consult operation manual for further details.









Note: Data published herein is intended as a guide only and shall not be construed to warrant applicability for lifting purposes. Crane operation is subject to the computer charts and operation manual both supplied with the crane.





TECHNICAL DESCRIPTION

TM 3851

Boom, Jib and Rotation

	Three-section full power fully synchronized telescopic keel boom	
	Boom length	21–51 ft
	Boom maximum tip height	61 ft
	Boom elevation angle range (min/max)	-8° / 82°
	Boom up/down time Boom extension/retraction time	25/16 seconds 43/20 seconds
	Boom head	Quick reeving
	Maximum tip height: boom with jib 18–29 ft	90 ft
	360° non-continuous rotation	

Operator Controls

	Hoist line pull	11,400 lb
	Hoist line speeds	163 ft/min
	Rope diameter	9/16"
	Overhaul ball 1 Sheave block 2 Sheave block	6.25 USt 17.5 USt 22.5 USt
	1 part line 2 part line 3 part line 4 part line	9,600 lb 19,200 lb 28,800 lb 38,400 lb
	Fully proportional Independent outrigger controls	





TECHNICAL DESCRIPTION

TM 3851

Understructure



Front: Link-type		
To outer edge of pad		21 ft 8 in
Rear: "A" pattern		
To outer edge of pad		10ft

Optional Features

- Two-stage jib
- Rotation resistant rope
- Multi-part load blocks
- Main hoist with 2 speed motor
- Radio remote controls
- One-man or two-man baskets
- Hoist drum tensioner
- Continuous rotation
- Oil cooler
- Single front bumper outrigger
- Hydraulic hose reel
- Tool box



NOTES

TM 3851

A large rectangular area with a light gray background and horizontal lines, intended for handwritten notes.



Effective Date: May 2013. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex® is a registered trademark of Terex Corporation in the USA and many other countries. Copyright 2013 Terex Corporation.

Terex Cranes, Global Marketing, Dinglerstraße 24, 66482 Zweibrücken, Germany
Tel. +49 (0) 6332 830, Email: info.cranes@terex.com, www.terexcranes.com



www.terexcranes.com

Brochure Reference: TC-DS-I-E-TM 3851-05/13



TEREX®

WORKS FOR YOU.™